



**QUICK OPENING & CLOSING HEAD**  
Easy to replace die sets.



CE



NEOELEC™  
**BPL062**

HYDRAULIC CRIMPING TOOL  
**IN LINE TYPE**

18V  
2Ah

**HEXAGONAL CRIMPING**  
**6 > 300 mm<sup>2</sup>**



> Identical force, stroke and capacities as the manual tool **D62** and the battery operated tools **BPE062** & **BPP062**.



**VERY LIGHT HEAD**  
Excellent ratio weight/capacities.




**COMPATIBLE DIE SETS**  
With **80 kN** & **130 kN** ranges.




**ROTATIVE HEAD**  
180°

<b>STROKE</b>	13 mm
<b>FORCE</b>	62 kN
<b>CRIMPING TIME</b> (depending on section)	3 to 5 s
<b>BATTERY CAPACITY</b> (for 185 mm <sup>2</sup> copper lug)	220 crimps
<b>DIMENSIONS</b> (L x l x h in mm)	128 x 75 x 395
<b>WEIGHT</b> (with battery)	3.250 kg



Die sets  
**6 > 300 mm<sup>2</sup>**



**DIE SETS** – Refer to **PAGES 88 – 96**.

> Common interchangeable die sets for **D62**, **BPE062**, **BPL062** & **BPP062** tools.

<b>APPLICATIONS</b>	<b>SECTIONS</b>
Copper lugs and sleeves – NFC 20-130	6 > 300 mm <sup>2</sup>
Copper or alu. lugs and sleeves – DIN 48083	KZ6 > KZ34
C-shaped connectors	C10 > C50
Pre-rounding die sets	25 > 240 mm <sup>2</sup>
Bare or insulated sleeves in copper or alu.	E54 > E280



<b>DIMENSIONS</b> (mm)	471 x 415 x 116
<b>WEIGHT</b>	2.050 kg

> Case and charger delivered with the tool.

> **NEOELEC™** accessories  
Refer to **PAGE 56 – 57**.